Biological Safety Cabinet Class I LX10BSC1

Email: info@labdex.com **website:** www.labdex.com

Description

This model is designed for work involving low to moderate-risk agents. With the negative pressure, personal protection is made possible by constant air movement into the work area. Equipped with a soft touch control panel, LED display, and UV lamp for sterilization. The Stable air flow system provides firm protection to people and the environment.

Specifications

Internal dimension (W x D x H)	540 x 385 x 440 mm
External dimension (W x D x H)	550 x 395 x 730 mm
HEPA filter	99.999% efficiency at 0.3μm
Airflow velocity	>0.3m/s
Noise	≤60dB
Illuminating lamp	4 W x 1, LED lamp
UV lamp	15 W x 1
Emission	253.7 Nanometers for most efficient decontamination
Main body construction	PMMA
Work table	304 stainless steel
Power supply	AC220V±10%, 50/60Hz; 110V±10%
Power consumption	150 W
Package dimension (W x D x H)	710 x 550 x 950 mm
Gross weight	40 Kg

Features

- Soft touch control panel
- LED display
- Having a 304 stainless steel work table that is easy to clean
- Stable airflow system
- UV lamp for sterilization

- Memory function in case of power failure
- This model is energy-saving and provides high efficiency with low noise

Applications

- Used for personal and environmental protection, but not for product protection.

Standard Accessories

Accessory no	Specifications
1	LED lamp
2	UV lamp x 2 Pcs

Optional Accessories

Accessory no	Specifications
1	Electric height adjustable base stand

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com